

NOTES:

Current Rating: 1.0AMP
Contact Resistance: 20mΩ Max
Withstand Voltage: 500V AC/Minute
Insulation Resistance: 1000MΩ Min
Operation Temperature: -40℃ to +105℃

Contact Material: Phosphor Bronze
Contact plating: Au Or Sn over Ni
Insulator Material: LCP+30%G.F UL94V-0

Ordering Information

6311 - 0XXX X D XX P N X 01

No.of Pins per
50=50PIN
68=68PIN

Contact Plating
S0=Gold Flash/Tin
S3=10u"Gold/Tin
S4=15u"Gold/Tin
S5=30u"Gold/Tin

Packing
A=Tray
T=Tube

Item	Pitch	Mating
Standard	1.27	6310
Alternate		

			OPERATION	DRAW	DATE	SCALE	FIT	PART NO.
			XX ±0.40	JYhuang	2012/11/13	UNIT	mm	6311-0XXXDXXPNX01
			XX ±0.25	CHECK	DATE	SIZE	A4	TITLE: 68P FEMALE SCSI D-SUB 180° DIP
A0	2012/11/13	NEW	XXX ±0.15			SHEET	1/1	
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	DIM	TOL	APPROVE	DATE	PROJ.

No.of Pins	Dimension		
	A	B	C
50	41.87	34.57	30.48
68	53.30	46.00	41.91

